



Backshelf Hoods

Exhaust only

[XBEP](#)

[XKEP](#)

[XXEP](#)

[XGEP](#)

Wall Style Canopy Hoods

Exhaust Only – Single Wall Front

[XBEW](#)

[XKEW](#)

[XXEW](#)

[XGEW](#)

[XWEW](#)

Exhaust Only – Double Wall Front

[XBDW](#)

[XKDW](#)

[XXDW](#)

[XGDW](#)

[XWDW](#)

Face Supply

[XBFW](#)

[XKFW](#)

[XXFW](#)

[XGFW](#)

[XWFW](#)

Face & Air Curtain Supply

[XBCW](#)

[XKCW](#)

[XXCW](#)

[XGCW](#)

[XWCW](#)

Single Island Style Canopy Hoods

Exhaust Only

[XBEV](#)

[XKEV](#)

[XXEV](#)

[XGEV](#)

Face Supply

[XBFV](#)

[XKFV](#)

[XXFV](#)

Non-Filtered Hoods

Heat & Fume

[XO](#)

Dishwasher Hoods

[XD1](#)

[XD2](#)

[XD3](#)



Performance and Sizing Availability for Models
XBEP, XXEP, XGEP, XKEP

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
450	105
600	130

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***		Height From Front Lower Edge of Hood (in)***		Side Over-Hang (in)***	Hood Set-Back (in)***
	Min	Max	Min	Max	Min	Max	Min	Max
450	3	16	23	36	10	36	0	12
600								

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section. Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.
*** Hood widths, height, side over-hang and hood set-back are available in 1 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Models

XBEW, XXEW, XGEW, XKEW

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
400	135
600	150
700	270

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***	
	Min	Max	Min	Max
400	3	16	39	72
600	3	16	39	72
700	5	16	39	72

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section.

Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.

***Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Model XWEW

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
400	135
600	150
700	270

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***	
	Min	Max	Min	Max
400	3	16	45	72
600	3	16	45	72
700	5	16	45	72

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section.

Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.

***Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Models
XBDW, XXDW, XGDW, XKDW

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
400	135
600	150
700	270

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***	
	Min	Max	Min	Max
400	3	16	39	72
600	3	16	39	72
700	5	16	39	72

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section.
Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.
***Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Model XWDW

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
400	135
600	150
700	270

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***	
	Min	Max	Min	Max
400	3	16	45	72
600	3	16	45	72
700	5	16	45	72

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section.
 Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.
 ***Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Models

XBFW, XXFW, XGFW, XKFW

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
400	135
600	150
700	270

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***	
	Min	Max	Min	Max
400	3	16	42	72
600	3	16	42	72
700	5	16	42	72

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section.

Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.

***Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Model XWFW

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
400	135
600	150
700	270

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***	
	Min	Max	Min	Max
400	3	16	51	72
600	3	16	51	72
700	5	16	51	72

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section. Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.
 ***Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Models
XBCW, XXCW, XGCW, XKCW, XWCW

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
400	135
600	150
700	270

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***	
	Min	Max	Min	Max
400	3	16	51	72
600	3	16	51	72
700	5	16	51	72

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section.
Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.
***Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Models
 XBEV, XXEV, XGEV, XKEV, XBFV, XXFV, XKFV

Max Cooking Surface Temp, °F	Minimum Exhaust Airflow (cfm/ft)*
400	135
600	150
700	270

*Exhaust airflow is capable of being as low as listed above.

Max Cooking Surface Temp, °F	Length (ft)**		Width (in)***	
	Min	Max	Min	Max
400	3	16	48	78
600	3	16	48	78
700	5	16	48	78

**Hoods lengths are available in 1 inch increments. Max length is the length of a single section.
 Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.
 ***Hood widths are available in 6 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Model
XO

Length (ft)*		Width (in)**	
Min	Max	Min	Max
2	16	24	72

*Hoods lengths are available in 1 inch increments. Max length is the length of a single section.

Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.

**Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.



Performance and Sizing Availability for Models
XD1, XD2, XD3

Length (ft)*		Width (in)**	
Min	Max	Min	Max
3	16	36	72

*Hoods lengths are available in 1 inch increments. Max length is the length of a single section.
Total hood lengths can be greater than 16 feet, but will be manufactured in multiple sections.
**Hood widths are available in 3 inch increments.

Please consult your Accurex representative or CAPS (Computer Aided Product Selection) program for other available dimensional configuration options.